

IMPRESSORA TÉRMICA
V320L



ESPECIFICAÇÕES

Print Width	72mm	Barcode types	PC347(Standard Europe)、Katakana、
Column capacity	576 dots/line 512 dots/line		PC850(Multilingual)、PC860 (Portuguese)、
Printing speed	200mm/s - 260mm/s		PC863(Canadian-French)、PC865 (Nordic)、
Interface	USB+Serial / Lan		West Europe、Greek、Hebrew、East Europe、
Printing paper	79.5±0.5mm	Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)
Line spacing	3.75mm (Adjustable by commands)		/CODE39/ITF/CODABAR/CODE93/CODE128
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns	Input buffer	64K bytes
Character size	ANK , Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots)	NV Flash	256 K bytes
		Power adptor	Input: AC 110V/220V, 50~60Hz
		Cash draw output	DC 24V/2.5A
		Cutter life	1.5 million outs
		Print head life	100km